



> PRINT > COPY > SCAN > FAX

ECOSYS M2040dn
ECOSYS M2540dn

B/W MULTIFUNCTIONALS
FOR A4 FORMAT

A PRODUCTIVITY BOOSTER THAT PAYS OFF.



These two devices are ready to become key players in your office. With a print speed of 40 pages per minute, short first print and first copy times and professional scanning features, including simultaneous scanning of both document sides, they will surely help boost the productivity in their respective workgroups. Their low TCO makes them a very affordable and reasonable choice. Toner and paper capacity are equally impressive too, with up to 7,200 pages from one toner cartridge and up to 850 pages with two optional paper feeders. And as is to be expected from any KYOCERA device, they are extremely reliable, meaning you can stay productive as long as you need to.

- > Up to 40 pages per minute in A4
- > Time to first copy and first print 6.4 sec.
- > Dual scan document processor supporting A6 originals
- > 1,200 dpi printing quality
- > Duplex unit for cost-saving double-sided printing
- > Up to 2 optional paper feeders for up to 850 sheets
- > Compact design with low-noise printing
- > Exceptionally low printing costs in its class



ECOSYS stands for ECOlogy, ECONomy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means toner is the only consumable for the first 100,000 pages. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility

ECOSYS M2040dn/ECOSYS M2540dn GENERAL

Technology: KYOCERA ECOSYS Laser
Control panel display: 5 line LCD display
Engine speed: Up to 40 pages A4 per minute
Resolution: 300 dpi, 600 dpi, 1,200 dpi
Duty cycle: Max. 50,000 pages per month
Warm-up time: Approx. 17 seconds or less
Time to first print: Approx. 6.4 seconds or less
Time to first copy: Approx. 6.4 seconds or less
CPU: 800 MHz
Memory: Standard 512 MB, max. 1,536 MB
Standard interface: USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Slot for optional SD/SDHC-Card
Dimensions (W x D x H): Main unit: 417 x 412 x 437 mm
Weight: Main unit: Approx. 19 kg
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption:
 Copy/Print: 661 W
 Ready mode: 21 W
 Sleep-mode: 1 W
Noise (Sound pressure level: ISO 7779/ISO 9296):
 Copy/Print: 48.3 dB(A) LpA
 Quiet mode: 44.1 dB(A) LpA
 Ready/Standby mode: Immeasurably low
 Sleep mode: Immeasurably low
Safety standards: GS, TÜV, CE
 This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
Input capacity: 100-sheet multi-purpose tray; 60–220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm – 216 x 356 mm) 250-sheet universal cassette; 60–163 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 – 216 x 356 mm). Max. input capacity with options: 850 sheets
Duplex functionality as standard: Double-sided printing: 60–163 g/m²; A4, A5, B5, Letter, Legal
Dual scan document processor: 50-sheet, 50–160 g/m², A4, A5, A6, B5, B6, Letter, Legal, Custom (100 x 148 to 216 x 356 mm)
Output capacity: Max. 150 sheet face down with paper full detection

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc
Emulations: PCL 6 (PCL 5e/PCL-XL), PostScript 3 (KPD L 3), PDF Direct Print, XPS/OpenXPS
Operating systems: All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other operating systems on request
Fonts/barcodes: 93 scalable fonts for PCL6/KPDL3, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

COPY FUNCTIONS

Max. original size: A4(Platen)/Legal(DP)
Continuous copying: 1–999***
Zoom range: 25–400% in 1% steps
Preset magnification ratios: 7 Reductions/5 Enlargements
Exposure mode: Manual: 9 steps
Image adjustments: Text + Photo, Photo, Text, Map
Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, priority print, program, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS

Functionality: Scan-to-e-mail (SMTP), Scan-to-FTP (FTP over SSL), Scan-to-SMBv3, Scan to USB Host, TWAIN scan (USB, network), WSD (WIA) scan (USB, network)
Scan speed: 40 ipm (300 dpi, A4, b/w, simplex), 23 ipm (300 dpi, A4, colour, simplex), 32 ipm (300 dpi, A4, b/w, duplex), 16 ipm (300 dpi, A4, colour, duplex)
Scan resolution: 300dpi x 300dpi, 200dpi x 200dpi(Default), 200dpi x 100dpi, 600dpi x 600dpi, 400dpi x 400dpi, 200dpi x 400dpi
Max. scan size: A4(Platen), Legal(DP)
Original recognition: Text + Photo, Photo, Text, Light Text/ Fine Line, Text (for OCR)
Scan file formats: TIFF, PDF, PDF/A-1, high compression PDF, encrypted PDF, JPEG, XPS
Compression method: MMR/JPEG
Features: Integrated address book, LDAP, encrypted data transfer, Blank sheet skip

FAX FUNCTIONS (ECOSYS M2540DN ONLY)

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: Less than 3 seconds
Scanning speed: 2 sec./sheet or less
Address book: 200 entries
Scanning densities:
 Normal: 200 x 100 dpi, Fine: 200 x 200 dpi, Superfine: 200 x 400 dpi, Ultrafine: 400 x 400 dpi
Maximum original size: A4, Legal
Compression method: JBIG, MMR, MR, MH
Features: Network fax, duplex transmission and reception, polling transmission and reception

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752
Toner-Kit TK-1170: toner yield 7,200 pages A4
 Starter toner: toner yield 3,600 pages A4

OPTIONS

PF-1100 Paper feeder (max. 2 units): 250 sheets; 60–163 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm – 216 x 356 mm)
Memory upgrade: MD3-1024: 1,024 MB
UG-33: ThinPrint support
USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available
CB-1100: Wooden cabinet

MODEL VARIATIONS

ECOSYS M2040DN/KL3: ECOSYS M2040DN incl. warranty extension KYOLife 3 years
ECOSYS M2540DN/KL3: ECOSYS M2540DN incl. warranty extension KYOLife 3 years


WARRANTY

1-year warranty** as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 100,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

KYO LIFE The up to 5-year on-site warranty extension for printer and options.



SEPT2016/ECOSYS/M2040dn/M2540dn/EMC



KYOCERA Document Solutions Europe B.V. – Branch Office Germany
 Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany
 Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100
www.kyoceradocumentsolutions.eu – info@deu.kyocera.com

KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri
 Chuo-Ku – Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.
 ** Depending on the country
 *** When optional memory installed

YOUR KYOCERA BUSINESS PARTNER

